



GRÜN EAE SAFEX MULTI HO



TOOLS



2x 24




ATTENTION:

When using the anchor device, observe the GRÜN safety instructions.
When mounting the anchor device, observe the assembly instructions.

Contents

1	Utilisation variants	3
2	Technical data	4
3	Assembly specifications EN 795	5
3.1	Substrate requirements	5
3.2	Structure and assembly of the anchor device	5
4	Documentation	6
5	Product labelling	6
6	Notes	7



Abbreviations	Meaning
EAE	Einzelanschlageinrichtung (Single anchor device)
SYS	Seil - S ystem (Lifeline system)
BEF	B efestigungsset (Fixing set)
ZUB	Z ubehör (Accessories)

ATTENTION:

To use the anchor device, observe the GRÜN safety instructions **(1)**.
To attach the anchor device, observe the installation instructions **(2)**.

Only the installation instructions from GRÜN apply.

Only the fixing materials supplied by GRÜN are permitted to be used.

Do not replace individual parts.

1 Utilisation variants




2 Technical data

Product specifications:


Requirement	Test centre	Marking	User
DIN EN 795:2012 CEN/TS 16415:2017	DEKRA Testing and Certification GmbH Persönliche Schutzausrüstung/Personal Protective Equipment Dinnendahlstr. 9 44809 Bochum - Germany		
abZ/aBG Z-14.9-725	Deutsches Institut für Bautechnik (DIBt) Kolonnenstr. 30 B 10829 Berlin - Germany		

Load direction:



- Standard construction height: 300mm bis 600mm
- Custom lengths: 700mm bis 1000mm
- Material: A2 stainless steel
- Footplate dimensions: 210mm x 250mm
- Hole pattern: 170mm x 210mm - ø11mm

Free support projection:



The subfloor must be part of the static basic construction.
In case of doubt, this should be checked by a structural engineer.

■ Assembly specifications according to EN795

EN 795

3 Assembly specifications EN 795



3.1 Substrate requirements

Installation must be carried out on suitable subfloors with adequate strength.

GRÜN recommendation:

Subfloor	Dimensions	
Wood ≥ C24	Minimum component thickness	100 mm
	Minimum edge distance	200 mm

3.2 Structure and assembly of the anchor device



- All 4 timber construction screws must be screwed in a stop-orientated manner.



4 Documentation

The installer is obliged to document the installation, including photos of details that will no longer be visible.

Installation documentation and maintenance documentation form available at:
(<https://gruen-gmbh.de/de/absturzschutz/download/>)



Digital documentation with GRÜN DOKU possible at:
(<https://documentation.gruen-gmbh.de>)



5 Product labelling

Type plate



Example illustration of labelling

- ① Manufacturer / Utilisation
- ② Product name
- ③ Observe installation instructions & safety instructions

Swivel eye (anchorage points)



Example illustration of labelling

- ④ Max. users
- ⑤ Serial number

- If the labelling of the anchorage device is no longer accessible/recognisable after installation, additional labelling must be provided in the vicinity.

MA_SAFEX_MULTI_HO_en_26_01

GRÜN

Spezialmaschinenfabrik für Dach, Bau und Straße
Siegener Straße 81-83
57234 Wilnsdorf / GERMANY

Tel. +49 (0) 271 - 39 88-0
Fax +49 (0) 271 - 39 88-159
E-Mail info@gruen-gmbh.de
www.gruen-gmbh.de



Urheberrechtshinweis

© Grün GmbH 2026. Alle Rechte vorbehalten. Diese urheberrechtlich geschützten Unterlagen dürfen - auch auszugsweise - nur mit vorheriger Genehmigung der GRÜN GmbH vervielfältigt, abgeändert oder in irgendeiner Form oder irgendeinem Medium weitergegeben oder in einer Datenbank oder einem anderen Datenspeichersystem gespeichert werden. Eine Verwendung ohne vorherige Genehmigung gilt als Verstoß gegen die jeweiligen Copyright-Bestimmungen.